

Screens to Fit Original Equipment

Screens to meet or exceed OEM specifications

Screens manufactured to fit OEM equipment are available. These screens are engineered to meet or exceed OEM specifications for screening media.

Many are available from stock. The list at right shows nominal screen sizes and the OCW or ICW (outside or inside) clamping widths that fit manufacturers equipment.

If you don't see the size you need here, measure your screen or equipment and call us toll free with the specifications.

For more information on measuring for proper screen fit...see **Inside Back Cover**.

NOTE: Compass Wire Cloth has contacted the manufacturers to verify these measurements. However there may be exceptions. If you feel your equipment requires a special screen size, consult your operation manual.

The ICW or OCW dimensions and degree of hook must be given when ordering. Check your operation manual or measure an old screen for the correct dimensions.

*These original equipment manufacturers sometimes use center hooking devices on their widest screens. This is called a split deck and may require one hook up and one hook down.

Original equipment screening media OCW & ICW

Outside clamping width in inches unless noted.

NOMINAL SIZES	3'-0"	4'-0"	5'-0"	6'-0"	7'-0"	8'-0"
Allis Minerals Systems	35	47	59	71	82	95
Barber-Greene	35	47	59	71	83	95
Cedar Rapids* (ICW)	34.5	46.5	58.5	71	86	98
Deister* (ICW)	33.5	45.5	57.5	69.5	81.5	--
ElJay* (ICW)	36.5	48.5	60.5	74.5	86.5	98.5
Hewitt-Robins New V-Series	39	51	63	75	87	99
JCI (ICW)	--	--	60.5	74.5	86.5	--
Kolberg	35	47	59	71	83	95
Kolman	36	48	60	72	--	--
Lippman	40	47	59	71	88	100
MERT Mfg, Inc. (Bonded Machine)	35	47	59	71	--	--
Pioneer Production Engineered Products	--	48 or 49	60 or 61	72	--	--
Seco* (ICW)	35	47	59	71	83	--
Simplicity	37	49	61	72.75	84.75	96.75
Telsmith	35	47	59	71	83	95
Thunderbird Incline	36.5	48.5	60.5	72.5	--	--
Horizontal	--	--	--	75	--	--
Universal Engineering	38.5	50.5	62.5	73.5	--	--